



DCT 800 VTL COILED TUBING UNIT



FEATURES:

- Easy Setup
- Highly Mobile
- On Board Mud Pump
- Self Contained
- Enclosed AC Cabin
- Automated Levelwind
- Workover Capabilities

The largest addition to the DCT line is the 800 VTL. A trailerized unit complete with an on-board mud pump, enclosed cabin, radio control setup and variable position mast.

Designed as a fit for purpose unit, the 800 VTL is well suited for the pursuit of low pressure shallow depth wells, and directional drilling. Easily adapted for use with e-line and hydraulic lines for downhole tool and communication functions, or in conjunction with the DCT speed connector for multipower transfer. In addition these connections are completely compatible with CT drilling Orienters. The unit comes equipped with an elite 80,000 pound capacity injector head, fluid swivel, automated levelwind system and CT stripper. head, fluid swivels, levelwind system, and CT stripper.

Contact us for additional information on this and other drilling rigs and support tools.

Amkin Manufacturing / An American Kinetics Inc. Company
Burton Texas USA 979.234.0010
www.amkininc.com

rev1912



DCT 800 VTL COILED TUBING UNIT

TECHNICAL DATA

Injector Head:	PUSH/PULL Rating Thrust (pull down) 40,000 lb Pullback (lift) 80,000 lb
Power Plant:	Deutz Diesel QSB
Fluids:	82 gal Hydraulic Tank 140 gal Diesel tank
Reel capacity:	4000 + ft 2.875 in. 5000 + ft 2.625 in. 6000 + ft 2.375 in. Others available
Fluid System:	Onboard Triplex Pump Option – Typical 350 hp High pressure swivel
Overall Dimensions:	Drill Angle: deg 45 - 90 Length: ~47 ft. Width: 8 ft 6 in. Height:: 13 ft 6 in.*

* Final travel height is dependent on customer setup